

RB ZIP-TILE™



RB Zip-Tiles are a new, revolutionary sport flooring alternative, manufactured from a composite of recycled rubber and custom-formulated, high strength, polyurethane binder.

RB Zip-Tiles are engineered so precisely that the intricate interlocking pattern virtually disappears as the tiles are installed. The result is the appearance of a monolithic surface accomplished with the ease of installing interlocking tiles.



INSTALLATION

RB Zip-Tiles can be installed easily over nearly any smooth surface including concrete, asphalt, wood or tile. No special tools are required. Transition strips are available.

WARRANTY

RB Zip-Tile is guaranteed to be free of manufacturing defects in material and workmanship for five years.

TYPICAL PROPERTIES



MATERIAL	Recycled SBR rubber from scrap tires and proprietary polyurethane binder	
RECYCLED CONTENT	Up to 88% post consumer content	
DIMENSIONS	28.5" X 28.5" X 3/8" (9.5mm)	
WEIGHT	11 1/4 lbs. per tile (2lbs. per sq. ft)	
APPEARANCE	Tiles are black or black with colored fleck accent	
DENSITY	ASTM D-3676	60 pcf
TEAR STRENGTH	ASTM D-624	80 pli min
ELONGATION	ASTM D-412	>145%
HARDNESS	ASTM D-2240 (Shore A)	60 +/-5